



MA-1212

MA-1212 Commercial Mixer Paging Amplifier

The MA-1200 series of professional rackmount mixer/amplifiers are designed for larger background music/paging and public address system installations where expandability and flexibility is the ticket. These new units are exceptional values, loaded with features and are easy to install in a variety of system designs.

The MA1212 features 10 balanced mic or line inputs all available with 24v phantom power and 2 auxiliary stereo summing inputs with 4 level sensitivity adjustment. 120 watts of amplifier power is available either into 70/100v or 4 ohm loads. Also included is a balanced line level output for adding additional power amplifiers. The unit also features 24 volt powered operation for emergency power requirements. An adjustable level telephone paging input along with a independently adjustable low power monitor output are included. Integrated rack ears allow for rack mounting without additional accessories.

Specifications

| | |
|---|--|
| Continuous rated power (1k Hz, THD 1%) 4Ω | 120 Watts |
| Electronics Type | Amplifier |
| Total harmonic distortion | < 0.5 % |
| Intermodulation Distortion (SMTPE) | < 0.5 % |
| Signal-to-noise ratio (A-weighted) | > 90 dB |
| Input Impedance (balanced) | 47 kΩ |
| Input Sensitivity | .75mV |
| Weight Net | 12.7 kg (28 lbs) |
| Dimensions (HxWxD) | 132.5 x 483 x 320 mm (5.22" x 19.02" x 12.6") |



Related Press Releases

[TENNESSEE CHURCH STEPS UP TO EV](#)

Downloads



[MA1206/1212 Users Manual](#)



[MA-1212 EDS](#)



[MA Series Brochure](#)



[MA-1212 High-Res Image](#)

[DYNACORD](#) | [DYNACORD ProAnnounce](#) | [Electro-Voice](#) | [IRISnet](#) | [Klark Teknik](#) | [Midas](#) | [Telex](#)